



EN 149:2001 + A1:2009

DONALD FFP2 NR D

CAT III

EUROPEAN PRODUCT




C€1437

Increased breathing efficiency!



Lower breathing resistance Thanks to the use of the new non-woven fabric,

the half-mask has much lower breathing resistance



Half-mask that has one of the lowest breathing levels on the market. Air flow of 95l/min is the approximate value of breath when working in heavier environments

*Graph of initia I breathing resistance before starting

work test with air flo w 95l/min









ABOUT HALF-MASK

The respirator DONALD FFP2 NR D is designed to protect respiratory system against harmful effect of dust, solid and liquid aerosols when OEL is ≥0,05 mg/m 3 and the concentration of dispersed phase of aerosol does not exceed, 10 x ŌEL (Occupational Exposure Limit), 10 = APF (Assigned Protection Factor), 12 = NPF (Nominal Protection Factor).

EXAMPLES OF APPLICATION

Medium toxic solids, asbestos, copper, barium, titanium, vanadium, chromium, manganese, hardwood, coal dust with free silica content higher than 10%, mining industry, chemical industry, metallurgic industry, welding, soldering, respirable dusts

HOW IT WORKS

The filtering half mask is composed mostly of the face part made of filtering material and accessories such as headbands, or exhalation valve, depending on the model. When air is drawn in, it passes through the filtration material where it is cleansed before being inhaled. Exhaled air passes through filtration material (in the masks without a valve) or through both the exhalation valve and the filtration material (in models with a valve). The cup of the mask should be well adjusted to the user's face.

STORAGE

Respirators must be kept in manufacturer's package (foil bag, carton), in conditions shown on pictograms.

WARRANTY

Respirators stored according to manufacturer's recommendations do not change their parameters within 60 months from the production date

PACAKING:

10 pcs/transparent plastic bag 20 pcs/box 480 pcs/carton 7680 pcs/pallet